

VERIFICATION STATEMENT

GLOBE Performance Solutions

Verifies **PM₁₀** and **PM_{2.5}** Efficiency Performance for

**TYMCO Model DST-4 Dustless
Regenerative Air Street Sweeper**

Developed by TYMCO, Inc.
Waco, TX, USA

Registration: **GPS-ETV_VR2026-03-31-DST4A**

In accordance with

ISO 14034:2016
Environmental Management —
Environmental Technology Verification (ETV)



Yogendra Chaudhry
CEO
GLOBE Performance Solutions

October 3, 2025
Vancouver, BC, Canada



Verification Body
GLOBE Performance Solutions
404 – 999 Canada Place | Vancouver, B.C | Canada | V6C 3E2

Performance Claim(s)

The TYMCO Model DST-4 Dustless Regenerative Air Street Sweeper was operated according to the vendor's specifications at an average speed of 4.1 km/h in a controlled space where no water or any other liquids were permitted. No water sprays or gutter broom shrouds were used in the testing.

The sweeper was delivered in its optimum balance of dry-dustless operational mode while also maximizing the pick-up and removal of test material (mean size of test material is 3 microns).

The final average performance indicators – at the 95% confidence interval – of the TYMCO Model DST-4 Dustless Regenerative Air Street Sweeper are as follows:

1. A removal efficiency of test material from surface of 89% ($\pm 2.1\%$);
2. Deposit of test material on sidewalk of 0.06% ($\pm 0.04\%$);
3. Maximum concentration of PM_{10} air contamination of 0.015 (± 0.005) $mg \cdot m^{-3} \cdot kg^{-1}$;
4. Total concentration of PM_{10} air contamination of 11.0 (± 2.3) $mg \cdot m^{-3} \cdot kg^{-1}$;
5. Maximum concentration of $PM_{2.5}$ air contamination of 0.011 (± 0.003) $mg \cdot m^{-3} \cdot kg^{-1}$; and
6. Total concentration of $PM_{2.5}$ air contamination of 7.5 (± 2.2) $mg \cdot m^{-3} \cdot kg^{-1}$.

Technology Description and Application

TYMCO Regenerative Air Dustless Sweeping Technology (DST) is designed to thoroughly clean roads and streets while minimizing the release of dust into the air. The street sweeper can have a positive environmental effect by reducing the amount of materials entering the storm sewers which may otherwise end up contaminating surface waters. Additionally, removal of particulate from streets may help reduce airborne contamination by such particulate matter, particularly on windy days.

The TYMCO Model DST-4 Dustless Regenerative Air Street Sweeper is a mid-sized street sweeper. The main components of TYMCO Regenerative Air Dustless Sweeping Technology (DST) are the blower, pickup head, pressurized hopper, multi-pass cylindrical centrifugal dust separator, and particulate air filters. The closed-loop regenerative air system uses a large blower to develop airflow. The air enters a distribution manifold that runs across the pickup head, which has a discharge opening that directs a high-velocity blast of air down and onto the pavement and into the cracks releasing dirt. The air and all captured dirt and debris are then drawn out of the pickup head through a hose and directed into the hopper.

After the debris-laden air stream is drawn into the large hopper, the air loses velocity allowing the larger debris to fall to the bottom. A screen at the top of the hopper prevents items such as leaves, paper, cans, and rocks from leaving the hopper. The air then enters the centrifugal dust separator. The multi-pass centrifugal dust separator further cleans the air as it spins on the curved wall of the centrifugal chamber skimming off dust particles and returning them into the hopper. The cleaned air is returned through the blower to the pickup head to start the regenerative air cycle again.

A small portion of the air leaving the blower is exhausted to atmosphere so that less air enters the pickup head than is being drawn off, thus maintaining the necessary vacuum in the pickup head. Prior to being exhausted, this small portion of air is further cleaned by being first run through a bank of small cyclone pre-cleaners and then through four membrane filters that have a Minimum Efficiency Reporting Value (MERV) 16 Rating, with the ability to capture a minimum of 95% of 0.30 micron and larger size particles.¹

¹ The TYMCO Model DST-4 has always used Torit-Tex® filter cartridges, as declared by the manufacturer, Donaldson Company, Inc. Independent testing carried out in accordance with the American Society of Heating, Refrigeration, and Air Conditioning Engineers [ASHRAE] 52.2 testing criteria, has reportedly determined these membrane filters to achieve a MERV 16 rating with the ability to capture greater than 95% of 0.3 micron and larger particles. Previous filter manufacturer-selected testing had rated the filter cartridge's performance as the ability to capture 99.999% of 0.50 micron and larger-sized particles. This Verification Statement has been updated to reflect the declared ASHRAE 52.2 testing results.

TYMCO Model DST-4 Dustless Regenerative Air Street Sweeper technology is engineered to allow the sweeper to perform in all types of weather conditions with no operator adjustments required.

Performance Conditions

The TYMCO Model DST-4 Dustless Regenerative Air Street Sweeper was tested at the Prairie Agricultural Machinery Institute (PAMI) facility (Test Agent) in Humboldt, Saskatchewan over three test days in June of 2008. The test facility was an enclosed tent about 80m x 11m. The test material was Camel-Wite®, manufactured by Debro Chemicals and Pharmaceuticals, a calcium carbonate-based powder with a mean diameter of about 3 microns. Approximately 274 kg was applied to the test track, which consisted of two strips, 2.75m x 30m each. The test agent conducted the testing and measurement according to the “PM₁₀ and PM_{2.5} Street Sweeper Efficiency Test Protocol” (City of Toronto, April 2008).

Verification

This verification was first completed in October 2008 and has been considered valid for subsequent renewal periods every three (3) years thereafter, subject to review and confirmation of the original performance and performance claims.

The original verification was completed by the ORTECH Environmental of Mississauga, Ontario as the Verification Entity using ETV Canada’s General Verification Protocol (February, 2007). The verification was based on information supplied by TYMCO, Inc., and the performance tests conducted by the Test Agent on the TYMCO Model DST-4 Regenerative Air Street Sweeper in June of 2008 according to the “PM₁₀ and PM_{2.5} Street Sweeper Efficiency Test Protocol” (City of Toronto, April 2008).

This ETV renewal is considered to meet the equivalency of an ETV verification completed using the International Standard **ISO 14034:2016 Environmental management -- Environmental technology verification (ETV)**

What is ISO 14034:2016 Environmental management – Environmental technology verification (ETV)?

ISO 14034:2016 specifies principles, procedures and requirements for environmental technology verification (ETV) and was developed and published by the *International Organization for Standardization (ISO)*. The objective of ETV is to provide credible, reliable and independent verification of the performance of environmental technologies. An environmental technology is a technology that either results in an environmental added value or measures parameters that indicate an environmental impact. Such technologies have an increasingly important role in addressing environmental challenges and achieving sustainable development.

**For more information on TYMCO
Model DST-4 Dustless Regenerative
Air Street Sweeper please contact:**

TYMCO, Inc.
225 E. Industrial Blvd.
Waco, Texas
76705 USA
Tel: 254-799-5546
Fax: 254-799-2722
info@tymco.com
www.tymco.com

**For more information on ISO 14034:2016 / ETV
please contact:**

GLOBE Performance Solutions
404 – 999 Canada Place
Vancouver, BC
V6C 3E2 Canada
Tel: 604-695-5018 /
Toll-Free: 1-855-695-5018
etv@globeperformance.com
www.globeperformance.com

Limitation of verification - Registration: GPS-ETV_2023-03-31_DST4A

GLOBE Performance Solutions and the Verification Expert provide the verification services solely on the basis of the information supplied by the applicant or vendor and assume no liability thereafter. The responsibility for the information supplied remains solely with the applicant or vendor and the liability for the purchase, installation, and operation (whether consequential or otherwise) is not transferred to any other party as a result of the verification.